



Pen Type Visual Fault Locator

BML-205

- ◆ Bright red laser at 650nm
- ◆ Pulsed and CW operation
- ◆ Standard AA alkaline batteries
- ◆ CE Qualified
- ◆ Fast locate the broken point
- ◆ Rugged and waterproof design
- ◆ 2.5mm universal connector



SPECIFICATIONS

BML-205	BML-205-1	BML-205-10	BML-205-15	BML-205-20	BML-205-25	BML-205-30
Output Power*	> 1mW	> 10mW	> 15mW	> 20mW	> 25mW	> 30mW
Dynamic Distance**	3~5 km	8~10 km	> 10km	> 10km	> 10km	> 10km
Wavelength	650nm ± 20nm					
Operation Mode	Pulsed(2Hz) and CW					
Connector	2.5mm UPP(or customize 1.25mm UPP)					
Size(H*W*D)	175mm * 26mm * 26mm					
Weight	80g					

* Tested by FOD1205H 650nm optical power meter

** Human eyes Min. sensitivity -120dBm, and 10dB/km loss of 650nm in fiber

ACCESSORIES

Standard	Optional
 Quick Guide*1	 Soft Bag*1
 Packing Box*1	 2.5mm to 1.25mm adapter



NEXT-Generation Network Measurement



ISO9001



ISO14001:2015